

[Home](#) ▶ [Equipment](#) ▶ [Loaders](#) ▶ [Compact Track Loaders](#) ▶ T770

# T770

## Compact Track Loader



Experience legendary performance with the T770, a top-selling compact track loader. Engineered to protect your uptime, this versatile machine delivers the performance you need to make light work of big projects, with an impressive rated operating capacity, powerful breakout forces and fast cycle times.

- Non-DPF Bobcat engine
- Durable undercarriage
- High-performance cooling
- Operator-friendly controls
- [View All Features](#)

**Starting at**  
**\$88,703 USD\*\***

**Special Offers**  
Lease a T770 compact track loader for as low as \$1,099 USD\* per month. Offers end June 30, 2025.

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)


[Find Dealer](#)

[Download Brochure](#)

## T770 Overview

- With 11 feet of vertical lift, the T770 is your ultimate jobsite partner for demanding applications. It’s designed to keep you digging, pushing, lifting and powering a wide range of attachments in all weather and ground conditions.
- The T770 protects your uptime with a non-DPF Bobcat engine, cold weather protection to prevent premature component wear, the Smart Cooling system for efficient operation in harsh working conditions, battery run-down protection, and design features that protect hoses, quick couplers and electronics.
- The optional automatic ride control is easily activated from inside the cab for greater comfort and to minimize bucket spillage.

Bobcat M3-Series Compact Track and Skid-Steer Loaders Walk-Around | Bobcat Loaders



## T770 Specs & Compare

| ⬆️ T770 Key Specifications     |
|--------------------------------|
| T770                           |
| Rated Operating Capacity (ISO) |
| 3,475 lb                       |
| Operating Weight               |
| 10515 lb                       |
| Ground Pressure (Rubber)       |
| 4.2 psi                        |
| Auxiliary Std Flow             |
| 23 gal/min                     |
| Auxiliary High Flow            |
| 36.6 gal/min                   |
| Joystick Control               |
| Optional                       |

| ⬆️ Engine            |
|----------------------|
| T770                 |
| Emissions Tier (EPA) |
| Tier 4               |
| Engine Cooling       |
| Liquid               |
| Engine Fuel          |
| Diesel               |
| Horsepower           |
| 92 hp                |
| Turbocharged Engine  |
| yes                  |

| ⬆️ Performance                 |
|--------------------------------|
| T770                           |
| Rated Operating Capacity (ISO) |

|                                 |
|---------------------------------|
| 3,475 lb                        |
| Operating Capacity (50% of Tip) |
| 4960 lb                         |
| Tipping Load                    |
| 9929 lb                         |
| Operating Weight                |
| 10515 lb                        |
| Travel Speed                    |
| 6.6 mph                         |
| Travel Speed (2-speed option)   |
| 10.7 mph                        |
| Ground Pressure (Rubber)        |
| 4.2 psi                         |

|            |
|------------|
| Capacities |
| T770       |
| Fuel Tank  |
| 43.8 gal   |

|                                |
|--------------------------------|
| Hydraulic System               |
| T770                           |
| System Relief @ Quick Couplers |
| 3,500 psi                      |
| Auxiliary Std Flow             |
| 23 gal/min                     |
| Auxiliary High Flow            |
| 36.6 gal/min                   |

|                             |
|-----------------------------|
| Dimension                   |
| T770                        |
| Length                      |
| 141.6 in                    |
| Length without Attachment   |
| 114.3 in                    |
| Length with Standard Bucket |
| 141.6 in                    |
| Width                       |
| 78 in                       |
| Width (with bucket)         |
| 80 in                       |
| Height                      |
| 81.3 in                     |
| Height with Operator Cab    |
| 81.3 in                     |
| Height to Bucket Hinge Pin  |
| 131.4 in                    |
| Reach @ Maximum Height      |
| 35.2 in                     |
| Turning Radius              |
| 88 in                       |
| Length of track on ground   |
| 63.7 in                     |
| Track Width                 |
| 17.7 in                     |

|                  |
|------------------|
| Features         |
| T770             |
| Joystick Control |
| Optional         |
| Air Conditioning |

|                              |
|------------------------------|
| Optional                     |
| Backup Alarm                 |
| Standard                     |
| BICS System (Interlock)      |
| Standard                     |
| Cab Heater                   |
| Optional                     |
| Operating Lights             |
| Standard                     |
| Suspension Seat              |
| Standard                     |
| Two Speed Travel             |
| Optional                     |
| Deluxe Instrumentation       |
| Optional                     |
| Engine Shutdown              |
| Standard                     |
| Hydraulic Bucket Positioning |
| Optional                     |
| High Flow Option             |
| Optional                     |
| Auxiliary Hydraulics         |
| Standard                     |
| Bob-Tach Attachment System   |
| Standard                     |
| Power Bob-Tach               |
| Optional                     |
| ACS (Switchable Controls)    |
| Optional                     |
| Ride Control                 |
| Optional                     |
| Horn                         |
| Standard                     |
| Cab Enclosure                |
| Optional                     |
| Adjustable Seat              |
| Standard                     |
| Sound Option                 |
| Optional                     |
| Rear Window                  |
| Standard                     |
| Top Window                   |
| Standard                     |
| Seat Belt                    |
| Standard                     |
| Spark Arrestor Muffler       |
| Standard                     |

## T770 Features & Benefits

Expand all ▾

- ▼

Productivity and Performance

14
- ▼

Durability and Uptime Protection

6
- ▼

Operator Comfort

12
- ▼

Maintenance and Serviceability

5
- ▼


Versatility and Attachments

4
- ▼

Digital Connectivity

2


## Special Offers



### Compact Track & Skid Steer Loaders Extended Warranty

For a limited time, select track loader and skid-steer loader models include full extended warranty coverage of 36 months/2,000 hours\*. Offer ends June 30, 2025.

[Offer Details >](#)



### Compact Track & Skid-Steer Loaders

As low as 0% for 60 months\* or rebates up to \$10,000 USD\* in lieu of financing. Offer ends June 30, 2025.

[Offer Details >](#)



### Compact Wheel Loaders


As low as 0% for 36 months\* or rebates up to \$10,000 USD\* in lieu of financing. Offer ends June 30, 2025.

[Offer Details >](#)



[View All Offers >](#)


## T770 Attachments



### 3-Point Adapter

Use with Category I and II implements.

[View Attachment >](#)




4 Options Available

### Angle Broom

Clear away dirt, dried mud, light snow and other debris.

[View Attachment >](#)



12 Options Available

### Auger

Augers are ideal for digging holes.

[View Attachment >](#)



[View All Attachments >](#)

# Related Models



### T450

|                                |         |
|--------------------------------|---------|
| Rated Operating Capacity (ISO) | 1490 lb |
| Operating Weight               | 6424 lb |
| Horsepower                     | 55 hp   |

[View Model >](#)



### T550

|                                |         |
|--------------------------------|---------|
| Rated Operating Capacity (ISO) | 1995 lb |
| Operating Weight               | 7557 lb |
| Horsepower                     | 68 hp   |

[View Model >](#)



### T595

|                                |  |
|--------------------------------|--|
| Rated Operating Capacity (ISO) |  |
| Operating Weight               |  |
| Horsepower                     |  |

[View Model >](#)

- 

[View All Compact Track Loaders >](#)



**WARNING:** *This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).*

*Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.*