<u>Home</u> ▶ <u>Equipment</u> ▶ <u>Loaders</u> ▶ <u>Skid-Steer Loaders</u> ▶ S62 Skid-Steer Loader

S62 Skid-Steer Loader



Tap to zoom









The radius-lift-path Bobcat® S62 provides enhanced performance, improved comfort and increased power for your heaviest lifting.

- Standard 5-inch color display panel
- Automatic heat and air conditioning
- Dual-direction bucket positioning

Request a Quote

Find a Dealer

Download Brochure

Download Leaflet

S62 Features

Expand all +

- **→ Performance** 14
- **→ Comfort** 9
- Uptime Protection 7
- Serviceability 5
- Attachment Versatility 3

S62 Specifications

Key Specifications

S62 Skid-Steer Loader

Horsepower

68 hp

Rated Operating Capacity (ISO)

1006 kg

Operating Weight

3123 kg

▲ Model

S62 Skid-Steer Loader

https://www.bobcat.com/oc/en/equipment/loaders/skid-steer-loaders/s62

Loader Series

R-Series

Rated Operating Capacity (50% of tipping load)

1006/2218 kg/lb.

Tipping Load (ISO 14397-2)

2012/4436 kg/lb.

Height to Bucket Hinge Pin

2908/114.5 mm/in.

2000/114.0 11111/111.

Size and Speed

Radius

Size and Speed

S62 Skid-Steer Loader

Operating Weight

3123/6884 kg/lb.

Width with Bucket

1727/68 mm/in.

Height with Cab

2045/80.5 mm/in.

Travel Speed - Low Range

11.9/7.4 kmh/mph

Travel Speed – High Range (optional 2-Speed travel)

17.7/11.0 kmh/mph

Engine

S62 Skid-Steer Loader

Horsepower

68/50.7 hp/kW

Type

Turbo Diesel

Fuel Tank Capacity

107.1/28.3 L/gal

Horsepower Management

Included with SJC Option

Control Options

S62 Skid-Steer Loader

Control Options

Bobcat Standard (foot pedals/steering levers)

Selectable Joystick Control (SJC)

Optional

Radio Remote Control (SJC required)

Optional

Hydraulic System

S62 Skid-Steer Loader

Hydraulic System Pressure (Standard & High Flow)

23.8-24.5/3450-3550 MPa/psi

Hydraulic Standard Flow

66.5/17.6 Lmin/gpm

Hydraulic High Flow (optional)

101.8/26.9 Lmin/gpm

Pressure Release Hydraulic Quick Couplers

Standard

Speed Management

Included with SJC Option

Dimensions

S62 Skid-Steer Loader

Rear of machine clearance radius

1692 mm

/26/25, 10:46 AM	S62 Skid-Steer Loader – Doosan Bobcat Oceania
Carry position machine clearance radius	
2027 mm	
Overall width	
1642 mm	
Tread(Track Gauge)	
1375 mm	
Bucket width	
1727 mm	
Overall operating height	
3772 mm	
Overall height	
2045 mm	
Angle of departure	
25 degrees	
Ground clearance	
189 mm	
Wheelbase	
1133 mm	
Length without attachment	
2718 mm	
Overall length	
3427 mm	
Maximum rollback - fully raised	
94 degrees	
Dump angle	
37 degrees	
Reach - fully raised	
518 mm	
Dump height	
2260 mm	
Maximum rollback - carry position	
31 degrees	
Height to hinge pin	

Similar Machines

2908 mm







\$550 Skid-Steer Loader

The Bobcat® S550 is the S450'

Operating Weight

\$100 Skid-Steer Loader

The Bobcat® S100 is the right size with enought lift capacity to help you in small spaces.

Horsepower	24.8 hp
Rated Operating Capacity (ISO)	457 kg
Operating Weight	1860 kg

S450 Skid-Steer Loader

If you're looking for an earth-mover that provides tremendous power and tons of

comfort, check out the Bobcat S450.	
Horsepower	61 hp

Horsepower Rated Operating Capacity (ISO) 894 kg Rated Operating Capacity (ISO)

2841 kg



Operating Weight